Vicoll


DATA SHEET


BUILDING


Connecto® I PVC grating - light grey colour -

class A15









FUNCTION:

The grating is designed to drain run-off water. In accordance with EN1433 standard and the marking C, it can be used in private areas for all building applications, the environment of home, parks and gardens in class A15.

■ DESCRIPTION:

This grating class A15 is injected in light grey PVC with anti-UV treatment.

CAN188

FIXCAN2

■ ACCESSORIES :

This grating can be installed with one type of drainage channel:

- Channel body Connecto lenght 1m width 200 in PP with PP edges - light grey: CAN188

To fix a grating, it's necessary to use two FIXCAN2 (set made up of 1 screw covered with zinc and 1 insert of zamak bichromate).

■ CHARACTERISTICS:

Resistance class: A15

Width: 199 mm Length: 500 mm Overall height: 39 mm Grating type: PVC

Drainage surface: 604 cm²/ml Opening dimensions: 10 / 157 mm

Weight: 1.3 kg

Bituminous area Paved area Concrete C20/25 G0 3330

■ IMPLEMENTATION:

- 1. See the installation scheme opposite with the channel CAN188.
- 2. If you don't use Connecto channel, please leave a space between gratings to allow a free expansion.

■ QUALITY - ENVIRONMENT :



DATE : July 2015



Head office and Plants: 37, rue Pierre et Marie Curie - BP 10966 - 49309 CHOLET Cedex

Email: export.nicoll@aliaxis.com